

Specifications (UAP-LR)

| UniFi AP Long-Range | |
|---------------------------|---|
| Dimensions | 200 x 200 x 36.5 mm |
| Weight | 290 g (430 g with Mounting Kits) |
| Networking Interface | (1) 10/100 Ethernet Port |
| Buttons | Reset |
| Antennas | 2 Integrated (Supports 2x2 MIMO with Spatial Diversity) |
| Wi-Fi Standards | 802.11 b/g/n* |
| Power Method | Passive Power over Ethernet (12-24V) |
| Power Supply | 24V, 0.5A PoE Adapter Included |
| Maximum Power Consumption | 6 W |
| Maximum TX Power | 27 dBm |
| BSSID | Up to Four Per Radio |
| Power Save | Supported |
| Wireless Security | WEP, WPA-PSK, WPA-TKIP, WPA2 AES, 802.11i |
| Certifications | CE, FCC, IC |
| Mounting | Wall/Ceiling (Kits Included) |
| Operating Temperature | -10 to 70° C |
| Operating Humidity | 5 - 80% Condensing |

| Advanced Traffic Management | |
|-----------------------------|---|
| VLAN | 802.1Q |
| Advanced QoS | Per-User Rate Limiting |
| Guest Traffic Isolation | Supported |
| WMM | Voice, Video, Best Effort, and Background |
| Concurrent Clients | 100+ |

| Supported Data Rates (Mbps) | |
|-----------------------------|---|
| Standards | Data Rates |
| 802.11n | 6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40) |
| 802.11b | 1, 2, 5.5, 11 Mbps |
| 802.11g | 6, 9, 12, 18, 24, 36, 48, 54 Mbps |

* 2.4 GHz

